

- [Home Theater](#)
- [Home Stereo](#)
- [Multimedia](#)
- [Car Audio](#)
- [Custom Install](#)
- [Pro Audio](#)
- [Drivers](#)

Home > Products > Drivers > Dome Tweeters > K1

K1

K1 Hi-end Tweeter



Overview

K1 is a new generation of high-frequency dome loudspeaker. Natural fiber high damping dome membrane, coated with special damping material. Natural and detailed sound performance. Flat frequency, could reach 25 KHz in high frequency range. Heat-resistant alloy(magnesium/aluminum) in frame, aluminum voice coil wire coat cooled. K1 has high -performance magnetic structure, a symmetrical driving magnetic field for l sensitivity, high magnetic density and strong faceplate with creative design. Detailed a

be used widely.

Specifications

General Data

Nominal Power Handling (Pnom)(W)	15
Max Power Handling (Pmax)(W)	30
Sensitivity (2.83v/1m)(dB)	92
Weight (M)(Kg)	0.9

Electrical Data

Nominal Impedance (Z)(Ω)	5
DC (Re)(Ω)	4.6

Voice Coil and Magnet Parameters

VC Diameter (mm)	25
VC Length (H)(mm)	2
VC Former	CCAW
VC Frame	Aluminum
Magnet System	Shielded
Magnet Former	Ferrite

T-S Parameters

Resonance Frequency (Fs)(Hz)	800
------------------------------	-----

Pictures of K1

