
F SERIES W23-1287SI



2*3" PP FULL RANGE

- **FULL RANGE DESIGN**
- **ABS BASKET, NEODYMIUM DESIGN**
- **ALUMINIUM PHASE PLUG COOLING**
- **PP CONE WITH SANTOPRENE SURROUND**
- **GOOD FOR CAR, HOME THEATER, MULTIMEDIA APPLICATION**
- **MAGNETICALLY SHIELDED**



DIAPHRAGM MTL	Natural color PPM
SURROUND MTL	Santoprene
NOMINAL IMPEDANCE	4 Ω
DCR IMPEDANCE	3.6Ω
SENSITIVITY 1W/1m	88 dB
FREQUENCY RESPONSE	150-20K Hz
FREE AIR RESONANCE	150 Hz
VOICE COIL DIAMETER	18.4 mm
AIR GAP HEIGHT	3 mm
RATED POWER INPUT	12 W
MAXIMUM POWER INPUT	24 W
FORCE FACTOR, BL	2.83 TM
MAGNET WEIGHT	Neodymium
MOVING MASS	1.53 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	678.656 MN^{-1}
EFFEC.PISTON AREA	0.0029 M^2
Levc	0.035mH
Zo	27ohm
X-max	0.9 mm
Vas	0.81 Litr
Qts	0.58
Qms	4.44
Qes	0.67

TB SPEAKERS
VOICE:886.2.26570282 FAX:886.2.26580166
E-MAIL :info@tb-speaker.com

CLOSE